

# TECHNICAL DATA SHEET

## 9.600.2

### Applications



CYCLIC



SOLAR



MARINE

### Electrical specification

Voltage:	<input type="text" value="12V"/>	(V)
Capacity C20:	<input type="text" value="125"/>	(Ah)
Capacity C5:	<input type="text" value="100"/>	(Ah)
RC:	<input type="text" value="235"/>	(min)

### Mechanical specification

Dimensional group:	<input type="text" value="-"/>	EN 50342-4:2010
ETN reference:	<input type="text" value="960 002 000"/>	
DIN reference:	<input type="text" value="96002"/>	
Sizes:	<input type="text" value="345x175x285"/>	(L x W x H)
Cell Layout:	<input type="text" value="0"/>	
Terminal Type:	<input type="text" value="1"/>	

### Container

<u>Case</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
	Bottom hold down	<input type="text" value="B0"/>	Handles	<input type="text" value="-"/>
<u>Lid</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
	Cover design	<input type="text" value="FLAT"/>	Handles	<input type="text" value="BLACK"/>
<u>Vent cap</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
	Type	<input type="text" value="FLAT"/>		

### Test details

Vibration resistance:

Endurance resistance:

### Separator:

Type:

Battery weight:  ± 1.00 (Kg)

Acid weight:  ± 0.50 (Kg)

Total battery weight:  ± 1.50 (Kg)

